# MSI

Making Dream Surfaces Attainable

# Antoni
Porcelain Collection

www.msisurfaces.com

## Colors

Cafe 6"x36"

Gris 6"x36"

Nero 6"x36"

Platinum 6"x36"

| Size | Thickness | CAFE | GRIS | NERO | PLATINUM |
|---|---|---|---|---|---|
| 6X36 Matte | 3/8" | NANTCAF6X36 | NANTGRI6X36 | NANTNER6X36 | NANTPLA6X36 |

| APPLICATIONS | Flooring | Counters | Wall | PEI Rating | Variation | COF | Breaking Strength | Water Absorption | Hardness |
|---|---|---|---|---|---|---|---|---|---|
| RESIDENTIAL | ● | ● | ● | IV | V3 | DCOF - > 0.42 Wet | > 275 lbf | < 0.5% | 7 |
| LIGHT COMMERCIAL | ● | ● | ● | | | | | | |
| HEAVY COMMERCIAL | | ● | ● | | | | | | |

| Freeze / Thaw | Chemical Resistance | Rectified/ Non-Rectified | Glazed / Non Glazed |
|---|---|---|---|
| Resistant | Resistant | Pressed | Glazed |

### Technical Information
Primary Colors: Black, Brown, Gray
Material Type: Porcelain Glazed
Finish: Matte

### Features At A Glance
• Offered in a 6x36 for more traditional wood floor look
• Pressed Wood Planks
• Ink Jet technology creates a life like wood look with realistic textures

### Installation
1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

**GREENGUARD**
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818
GOLD

**Disclaimer:**

*Wet Cutting Instruction:* We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.