

# MSI

Making Dream Surfaces Attainable



Carolina Timber  
Porcelain Collection

[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Beige 6"x24"



Gray 6"x24"



Saddle 6"x24"



White 6"x24"

Size	Thickness	BEIGE	GRAY	SADDLE	WHITE
6x24	3/8"	NCARTIMBEI6X24-N	NCARTIMGRE6X24-N	NCARTIMSAD6X24-N	NCARTIMWHI6X24-N
6x36	3/8"	NCARTIMBEI6X36-N	NCARTIMGRE6X36-N	NCARTIMSAD6X36-N	NCARTIMWHI6X36-N

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	6
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

Carolina Timber is a wood plank line with a contemporary look in very rich color tones. The four colors offered Beige, Grey, Saddle and White all have the look and feel of expensive hard woods with a hand rubbed oil finish. This line has the veining and graining of rich exotic tiger wood with lights and darks in all of the colors.

Technical Information

Primary Colors: Beige, Gray, Saddle, White  
Material Type: Glazed Porcelain  
Finish: Matte  
Matte: Hardness / Mohs 7

Features At A Glance

- Porcelain 6x24 and 6x36 planks
- Rich ink jet technology with over 20 faces
- Very price competitive with the look of a much higher priced tile line
- Four rich contemporary colors

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.