

Colors







Grayseas 8"x40" Nutmeg 8"x40" Taupe 8"x40"

| Size | Thickness | GRAYSEAS | NUTMEG | TAUPE | |
|------|-----------|-------------|-------------|-------------|--|
| 8x40 | 3/8" | NCELGRA8X40 | NCELNUT8X40 | NCELTAU8X40 | |

| APPLICATIONS | Flooring | Counters | Wall | PEI Rating | Variation | COF | Breaking Strength | Water Absorption | Hardness |
|------------------|----------|----------|------|------------|-----------|-------------------|----------------------|---------------------|----------|
| RESIDENTIAL | • | • | • | | | | | | |
| LIGHT COMMERCIAL | • | • | • | III | V2 | DCOF - < 0.42 Wet | < 275 LBF | > 0.5% | 5 |
| HEAVY COMMERCIAL | | • | • | | | | | | |

| Freeze / Thaw | Chemical Resistance | Rectified/ Non-Rectified | Glazed / Non Glazed |
|---------------|---------------------|--------------------------|---------------------|
| Non-Resistant | Resistant | Pressed | Glazed |

This wood tile flooring works well for design styles from traditional to modern as it provides a timeless backdrop to any space. This wood tile is perfect for countertops, walls, and floors wherever the look of hardwood is desired, but the durability of tile is required.

Technical Information

Primary Colors: Gray, Brown Material Type: Ceramic

Finish: Matte

Features At A Glance

- · Available in a 8x40
- Pressed Edges and Ink Jet Technology
- Beautiful Contemporary Wood Plank Look

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

