

# MSI

Making Dream Surfaces Attainable



Cemento  
Porcelain Collection  
[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Napoli 12"x24"



Novara 12"x24"



Treviso 12"x24"

Size	Thickness	NAPOLI	NOVARA	TREVISO
12x24	3/8"	NCEMNAP1224-N	NCEMNOV1224-N	NCEMTRE1224-N

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				III	V3	SCOF - > 0.60 Wet DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	6
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

A modern mix of high style and design, the Cemento line offers the latest gray colors in a concrete style that will update any space. Inspired by the look of actual concrete, these monochromatic tiles offer a quiet drama that's stunning. Offered in a rectangular tile, this tile will create that modern flair that will enable a range of creative combinations.

Technical Information

Primary Colors: Gray  
Material Type: Glazed Full Body Porcelain  
Finish: Matte  
Polished: Hardness / Mohs 5  
Matte: Hardness / Mohs 7

Features At A Glance

- Rectified Glazed Porcelain
- As a Full Body Porcelain, can be used for all residential as well as modern commercial applications

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.