

Colors













Ardesia Black 6"x24"

Carrara White 6"x24"

Nora Cream 6"x24"

Nora Ice 6"x24"

Nora Sterling 6"x24"

Palisade Grey 6"x24"



Rocky Gold 6"x24"

Size	Thickness	ARDESIA BLACK	CARRARA WHITE	NORA CREAM	NORA ICE	
6x24	3/8" NARDBLK6X24		NCARWHI6X24	NNORCRE6X24	NNORICE6X24	

Size	Thickness	NORA STERLING	PALISADE GREY	ROCKY GOLD		
6x24	3/8" NNORSTE6X24		NPALGRE6X24	NROCGOL6X24		

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Freeze/Thaw	Breaking Strength	Water Absorption	Hardness	Chemical Resistance
RESIDENTIAL			•								
LIGHT COMMERCIAL			•	IV	V4	DCOF - > 0.42 wet	Resistant	> 275	< 0.5%	7	Resistant
HEAVY COMMERCIAL			•								

Our Dekora line gives you everything you love about ledger panels, but without any of the maintenance. Offering 5 different porcelain ledger panels, feel free to decorate that outdoor island grill or frame your fireplace in the simple beauty of Dekora line. These panels come in a familiar 6"X24" size to fit perfectly into your outdoor or indoor design.

Technical Information

Primary Colors: Beige, Gray, Gold Material Type: Glazed Porcelain

Finish: Matte

Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- Stone ledger panel looks created with porcelain
- Classic 6X24 sizing in 5 different colors
- Ink Jet technology with 3D punch for realistic stacked stone looks

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.