

MSI

Making Dream Surfaces Attainable



Durban
Porcelain Collection

www.msisurfaces.com

Colors



White 12"x24"



Grey 12"x24"



Anthracite 12"x24"

| Size | Thickness | WHITE | GREY | ANTHRACITE |
|----------------|-----------|----------------|----------------|----------------|
| 12X24 Matte | 3/8" | NDURWHI1224 | NDURGRE1224 | NDURANT1224 |
| 12X24 Polished | 3/8" | NDURWHI1224P | NDURGRE1224P | NDURANT1224P |
| 24X48 Matte | 3/8" | NDURWHI2448 | NDURGRE2448 | NDURANT2448 |
| 24X48 Polished | 3/8" | NDURWHI2448P | NDURGRE2448P | NDURANT2448P |
| 2X2 | 3/8" | NDURWHI2x2 | NDURGRE2x2 | NDURANT2x2 |
| 3X24 | 3/8" | NDURWHI3x24BN | NDURGRE3x24BN | NDURANT3x24BN |
| 3X24 | 3/8" | NDURWHI3x24BNP | NDURGRE3x24BNP | NDURANT3x24BNP |

| APPLICATIONS | Flooring | Counters | Wall | PEI Rating | Variation | COF | Breaking Strength | Water Absorption | Hardness |
|------------------|----------|----------|------|------------|-----------|---|-------------------|------------------|----------|
| RESIDENTIAL | ● | ● | ● | III | V3 | DCOF < 0.42 Polished DCOF > 0.42 Matte | > 275 lbf | < 0.5% | 7 |
| LIGHT COMMERCIAL | ● | ● | ● | | | | | | |
| HEAVY COMMERCIAL | | | ● | | | | | | |

| Freeze / Thaw | Abrasion Resistance | Chemical Resistance | Rectified/ Non-Rectified | Glazed / Non Glazed |
|---------------|---------------------|---------------------|--------------------------|---------------------|
| Resistant | IV | Resistant | Rectified | Glazed |

Enjoy a more calming aesthetic looks. These natural stone porcelain tiles are durable and give an organic feel to any space. Available in 3 sizes and 3 colorways. Bullnose also available.

Technical Information

Primary Colors: White, Gray, Black

Material Type: Porcelain

Finish: Polished, Matte

Polished: Hardness / Mohs 5

Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer : Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Features At A Glance

- 3 Color In a Marble Look
- Available In Matte And Polished Finishes

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 24" Bullnose

