

MSI

Making Dream Surfaces Attainable



Eramosa
Porcelain Collection

www.msisurfaces.com

Colors



Beige 12"x24"



Grey 12"x24"



Silver 12"x24"



White 12"x24"

Size	Thickness	BEIGE	GREY	SILVER	WHITE
12x24	3/8"	NERABEI1224	NERAGRE1224	NERASIL1224	NERAWHI1224
3x18	3/8"	NERABEI3X18BN	NERAGRE3X18BN	NERASIL3X18BN	NERAWHI3X18BN

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				IV	V3	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	8
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

Named after the glamorous Canadian stone, the Eramosa series is a non-rectified porcelain tile that is a glamazon in its own right. Dramatic linear veining creates a striped appearance and a textural quality that you can feel on the surface. Eramosa is available in one size, 12"x24", and four chic colors that are sure to turn heads.

Technical Information

Primary Colors: Beige, Grey, Silver, White
Material Type: Glazed Porcelain, Non-Rectified
Finish: Matte finish with texture
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Features At A Glance

- Uniquely Multi-Styled Contemporary to Rustic
- Glazed Porcelain
- Ink Jet Technology

Trim



3" x 18" Bullnose

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.