



Making Dream Surfaces Attainable

Prescott™ Collection By MSI

Total thickness	6.5MM
Core thickness	5.5MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 21 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	\geq 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Uniclic
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	5-year

The Prescott™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife™ products.



Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	20 mil
Plank size	7" x 48"
Bevel	Painted/Beveled
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 21 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	\geq 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Uniclic
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	5-Year

The Andover™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which induces high variation designs. It is recommended that any consumer go to msisurfaces.com or view a display sample with room scene to see the high color variation. It also is recommended that a consumer use a qualified installer who works with a recommended dealer, that will follow the installation instructions for Everlife™ products.



Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	9" x 60"
Bevel	Painted/Beveled
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 21 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	\geq 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Uniclic (long side) / Drop-lock (short side)
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	6-Year
Commercial Warranty	N/A

The XL Cyrus™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which induces high variation designs. It is recommended that any consumer go to msisurfaces.com or view a display sample with room scene to see the high color variation. It also is recommended that a consumer use a qualified installer who works with a recommended dealer, that will follow the installation instructions for Everlife™ products.



Total thickness	5MM
Core thickness	4MM
XPE Backing	1MM
Wear Layer	12 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC ≥ 21 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	≥0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Installation System	Uniclic
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	6-Year
Commercial Warranty	N/A

The Cyrus™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which induces high variation designs. It is recommended that any consumer go to msisurfaces.com or view a display sample with room scene to see the high color variation. It also is recommended that a consumer use a qualified installer who works with a recommended dealer, that will follow the installation instructions for Everlife™ products.



Total thickness	2.5MM
Wear Layer	20 mil
Plank size	7" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 53 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 23 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	\geq 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Certifications	FloorScore & Greenguard
Residential Warranty	Lifetime
Light Commercial Warranty	10-Year
Commercial Warranty	5-year

The Wilmont™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife™ products.

Total thickness	2MM
Wear Layer	12 mil
Plank size	6" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM ² , NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 51 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC ≥ 23 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	≥0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Very Good
Certifications	FloorScore & Greenguard
Residential Warranty	25-year
Light Commercial Warranty	6-Year
Commercial Warranty	N/A

The Glenridge™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife™ products.



Total thickness	2MM
Wear Layer	6 mil
Plank size	6" x 48"
ASTM F2199 (Dimensional Stability)	Passes
ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM F1514 (Heat Stability)	Passes
ASTM F1515 (Light Stability)	Passes
ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)	<450
ASTM (E492-09 / ASTM 989-06)	71 - drop ceiling / 51 - 6" slab
ASTM E2179 (Impact Sound Reductions)	Δ IIC \geq 23 dB
ASTM F925 (Resistance to Chemicals)	Passes
ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
ASTM D2047 (Coefficient of Friction)	\geq 0.6 (Dry)
Scratch/Scuff/Abrasion Properties	Good
Certifications	FloorScore & Greenguard
Residential Warranty	15-year
Light Commercial Warranty	N/A
Commercial Warranty	N/A

The Katavia™ Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife™ collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife™ products.