

# MSI

Making Dream Surfaces Attainable



Focus  
Porcelain Collection  
[www.msisurfaces.com](http://www.msisurfaces.com)

## Colors



Glacier 12"x24"

Graphite 12"x24"

Size	Thickness	GLACIER	GRAPHITE
12x24	3/8"	NFOCGLA1224-N	NFOCGRA1224-N
2x2	3/8"	NFOCGLA2X2-N	NFOCGRA2X2-N
3X18	3/8"	NFOCGLA3X18BN-R	NFOCGRA3X18BN-R

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V2	DCOF - < 0.42 Wet	> 275 lbf	< 0.5%	5
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

Designers of fashion and interiors can't seem to get enough of mixing and harmonizing with pattern. Translate the trend to floors and walls with the Focus series. Thin directional stripes make a contemporary statement in rectified porcelain. The 12"x24" inch tiles come in Glacier, Khaki, Olive and Graphite and mix and match beautifully with the Dimensions and Loft series.

### Technical Information

Primary Colors: Beige, Gray  
 Material Type: Glazed Porcelain  
 Finish: Matte  
 Polished: Hardness / Mohs 5  
 Matte: Hardness / Mohs 7

### Features At A Glance

- Contemporary Fabric Look
- Glazed Porcelain
- Inkjet Printing
- Rectified for Precision Installation

### Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

### Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.

### Trim



3" x 18" Bullnose

