



Legend Porcelain Collection

www.msisurfaces.com

Colors







Grey 12"x24"

Moka 20"x20"

White 12"x24"

Size	Thickness	GREY	МОКА	WHITE
12x24	3/8"	NLEGGREY1224	NLEGMOKA1224	NLEGWHIT1224
20x20	3/8"	NLEGGRE2020	NLEGMOK2020	NLEGWHI2020
3x12 Bullnose	3/8"	NLEGGRE3X12BN	NLEGMOK3X12BN	NLEGWHI3X12BN
2x2 Mosaic	3/8"	NLEGGRE2X2	NLEGMOK2X2	NLEGWHI2X2

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL		۲	۲						
LIGHT COMMERCIAL	۲	۲	۲		V4	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
HEAVY COMMERCIAL			۲						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

Inspired by crosscut travertine, the Legend Collection offers a beautiful natural stone look in affordable and virtually maintenance free porcelain. This matte finish collection features gorgeous go with anything hues including light and airy gray, warm beige, and rich white, in some of today's most sought after sizes (12"X24" and 20"X20"). For use as wall and floor tile, it's highly versatile and an excellent choice when the look of natural stone is desired but durable, easy to clean, and low maintenance tile is preferred. Bring interest, depth, and sophistication to your project with the Legend Collection.

Technical Information

Primary Colors: White,Grey,Brown Material Type: Porcelain Finish: Matte Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- 3 different colors in 12x24 and 20x20
- High quality Ink Jet technology

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement. Trim



3" x 12" Bullnose



Disclaimer : Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.