

# Colors



MARZA PEARL

MARZA PEARL 4"x12"

Size 1/12

MARZA COBALT 4"x12"

Thickness

MARZA AQUA 4"x12"

MARZA COBALT

MARZA RUST 4"x12"

MARZA AQUA

4x12	3	3/8"	NMARPE	A4X12G	NMARCO	)B4X12G	NMAF	AQU4X12G	NMARRUS4X12G
APPLICATIONS	Backsplash	Wall	Variation	С	OF	Break Stren	-	Water Absorption	Hardness
RESIDENTIAL	•	•							
LIGHT COMMERCIAL	•	•	V4	N	I/A	< 275	5 lbf	< 0.5%	3
HEAVY COMMERCIAL	•	•							

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Non-Resistant	Resistant	Pressed	Glazed

Marza Subway Tiles features have a striking blend of tones that are ONE-OF-A-KIND addition to any kitchen backsplash, shower surround, or accent wall. Earthy brown tones, blues and greens, creamy whites, gold, bronze, copper and grays with a glossy finish that provides an extremely delicate or refined quality. These 4"x12" tiles are easy to clean and maintain. Marza is versatile, allowing for design flexibility and creative installations in your kitchen, shower, bath surround, and many more wall applications.

### **Technical Information**

Primary Colors: White, Blue, Green and Brown

Material Type: Ceramic

Finish: Glossy

### Features At A Glance

- 4 colors
- Earthy Tones

# Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



MARZA RUST

### Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.