

# MSI

Making Dream Surfaces Attainable



Napa  
Ceramic Collection  
[www.msisurfaces.com](http://www.msisurfaces.com)

## Colors



Beige 12"x24"



Gray 12"x24"

Size	Thickness	BEIGE	GRAY
12x24 Matte	3/8"	NNAPBEI1224	NNAPGRA1224
12x12 Matte	3/8"	NNAPBEI1212	NNAPGRA1212
2x2 Matte	3/8"	NNAPBEI2X2	NNAPGRA2X2
3x24 BN	3/8"	NNAPBEI3X24BN-K	NNAPGRA3X24BN-K

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	DCOF - > 0.42 Wet	< 275 lbf	> 0.5%	7
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL			●						

Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Rectified	Glazed

Inspired by cross cut travertine, the Napa Collection offers a beautiful natural stone look in affordable and virtually maintenance free ceramic. This matte finish collection features gorgeous go with anything hues, including light and airy gray, warm beige, and rich brown, in some of today's most sought after sizes. Suitable as wall tile and floor tile, it is the perfect choice when the look of natural stone is desired but durable, easy to clean, and low maintenance tile is preferred.

### Technical Information

Primary Colors: Beige, Brown, Gray

Material Type: Ceramic

Finish: Matte

### Installation


1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

### Features At A Glance

- Different Size including Large format and bullnose
- Available in 2 Different colors

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

### Trim



3" x 24" Bullnose

### Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a un polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.

