

# MSI

Making Dream Surfaces Attainable



# ONYX

Porcelain Collection

[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Onyx Grigio 12"x24"



Onyx Ivory 12"x24"



Onyx Sand 12"x24"

Size	Thickness	ONYX GRIGIO	ONYX IVORY	ONYX SAND
12x24 Matte	3/8"	NONYGRI1224-N	NONYIVO1224-N	NONYSAND1224-N
12x24 Polished	3/8"	NONYGRI1224P-N	NONYIVO1224P-N	NONYSAN1224P-N
24x24 Matte	3/8"	NONYGRI2424-N	NONYIVO2424-N	NONYSAN2424-N
24x24 Polished	3/8"	NONYGRI2424P-N	NONYIVO2424P-N	NONYSAN2424P-N
3x18 Bullnose	3/8"	NONYGRI3X18BN-R	NONYIVO3X18BN-K	NONYSAN3X18BN-R
3x18 Bullnose Polished	3/8"	NONYGRI3X18BNP-N	NONYIVO3X18BNP-N	NONYSAN3X18BNP-N
2x4 Polished	3/8"	NONYGRI2X4P-N	NONYIVO2X4P-N	NONYSAN2X4P-N
2x2 Matte	3/8"	NONYGRI2X2-N	NONYIVO2X2-N	NONYSAN2X2-N
2x2 Polished	3/8"	NONYGRI2X2P-N		NONYSAN2X2P-N

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V4	< 0.42 Polished > 0.42 Matte	> 275 lbf	< 0.5%	6
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Abrasion Resistance	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	IV	Resistant	Rectified	Glazed

Acquire the jaw-dropping beauty of natural onyx at a more palatable price point with the porcelain Onyx Ivory. The rectified inkjet tile is an elegant interpretation of the natural stone that requires virtually no maintenance. The series is available in an impressive array of sizes: 12"x24", 24"x24" and 3"x18" bullnose.

Technical Information

Primary Colors: Beige  
Material Type: Porcelain  
Finish: Polished & Matte  
Polished: Hardness / Mohs 5  
Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.

Features At A Glance

- 3 colors 12x24, 24x24 and a 3x18 Bullnose
- High quality Inkjet technology
- Competitively Priced Polished Tile

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 18" Bullnose

