

Colors



Cream 24"x24"

Graphite 24"x24"

Grey 2"x10"

Olive 24"x24"

Size		Thicknes	S	CRE	CREAM		GRAPHITE		GREY		OLIVE		
12x24		3/8"		NOPTCI	RE1224		NOPTGRA1224		NOPTGRE1224		NOPTOLI1224		
12X24 POLISHED		3/8"		NOPTCR	RE1224P		NOPTGRA1224P		NOPTGRE1224P		NOPTOLI1224P		
12X24 TEXTURED		3/8"		NOPTCRE	TEX1224	4 NOPTGRA		TEX1224	NOPTGRETEX1224		NOPTOLITEX1224		
24X24		3/8"		NOPTCRE2424			NOPTGRA2424		NOPTGRE2424		NOPTOLI2424		
24X24 POLISHED		3/8"		NOPTCR	E2424P		NOPTGRA2424P		NOPTG	NOPTGRE2424P		NOPTOLI2424P	
2X2 MATTE MOSAIC		3/8"		NOPTC	RE2X2		NOPTGRA2X2		NOPT	NOPTGRE2X2		NOPTOLI2X2	
2X2 POLISHED MOSAIC		3/8"		NOPTC	RE2X2P		NOPTGRA2X2P		NOPTO	NOPTGRE2X2P		NOPTOLI2X2P	
4X24 MATTE SBN		3/8"		NOPTCR	E4X24BN		NOPTGRA4X24BN		NOPTG	NOPTGRE4X24BN		NOPTOLI4X24BN	
4X24 POLISHED SBN		3/8"		NOPTCRE	E4X24BNP		NOPTGRA4X24BNP		NOPTGRE4X24BN		NOPTOLI4X24BNP		
APPLICATIONS	Flooring	g Counters	Wall	PEI Rating	Variation		COF	Freeze/ Thaw	Breaking Strength	Water Absorption	Hardness	Chemical Resistance	
RESIDENTIAL	۲		۲			DCOF							
LIGHT COMMERCIAL	T COMMERCIAL		۲	V	V2	Matte - > 0.42 wet Polished - < 0.42 wet Textured - > 0.60 wet		Resistant	> 275	< 0.5%	8	Resistant	
HEAVY COMMERCIAL			۲										

MSI's first "thru body" commercial line was worth the wait. This Optima line is designed to enhance any commercial space to its ultimate potential. Optima offers a classic cement look in standard 12"X24" in Matte, Polished, and a unique Textured finish, as well a large square format 24"X24" in both Matte and Polish. Optimize your next commercial project with any of the four colors of this classic line.

Technical Information

Primary Colors: Cream, Graphite, Grey, Olive Material Type: Unglazed Porcelain Finish: Matte, Polished and Textured

Features At A Glance

tile displacement.

- Optima is offered in 4 colors, 3 finishes, and 2 sizes, along with coordinating 4X24 Bull Nose and 2X2 Mosaic
- Offers a unique Textured finish in the 12X24 size for exterior use
- Cement look thru body commercial line

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended. Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and

Trim

4" x 24" Bullnose



Disclaimer:

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns. *No claims accepted after tile installation.