

Colors



Bianco 6"x36"



Fog 6"x36"



Chestnut 6"x36"



Smoke 6"x36"



Cognac 6"x36"



Walnut 6"x36"

Size	Thickness	BIANCO	CHESTNUT	COGNAC	FOG	SMOKE	WALNUT
6x36 Matte	3/8"	NPALBIA6X36	NPALCHE6X36	NPALCOG6X36	NPALFOG6X36	NPALSM06X36	NPALWAL6X36

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	•	•							
LIGHT COMMERCIAL	•	•	•	IV	V3	COF - > 0.42 Wet	> 275 lbf	< 0.5%	7
HEAVY COMMERCIAL		•	•						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed	
Resistant	Resistant	Pressed	Glazed	

Add warmth and character, patina and beauty with Palmetto. Fashioned from the latest in high definition ink jet technology, this gorgeous series captures an intricately natural wood look in dependable porcelain. Palmetto is inspired by the rich colors of authentic wood floors and modernized with the most current color glazes. Palmetto is sure to complement any interior space from a modern condo to a traditional villa.

Technical Information

Primary Colors: Brown, Gray Material Type: Porcelain

Finish: Matte

Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly

recommended.

Features At A Glance

- Luxurious porcelain (Matte) tiles with authentic marble looks and colorations
- Six great colors in a wide variety of sizes and trims
- · High Definition Ink Jet Technology

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.