



# What's In Flows Out

## MSI's Indoor/Outdoor Collection

# MSI

Making Dream Surfaces Attainable

# PRAIA

## PORCELAIN


[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Carrara 12"x24"



Crema 12"x24"



Grey 12"x24"



Carrara Paver 24"x24"



Crema Paver 24"x24"



Grey Paver 24"x24"

**Designers are Buzzing** The transitional living trend is here to stay, so here's the green light to start planning your dream space with MSI's industry-leading indoor-to-outdoor porcelain tile collections.

**Accessible Assortment** Authentic natural stone looks like marble, travertine, slate, and limestone to wood and concrete looks, we offer a wealth of indoor-to-outdoor tile and pavers options.

**Flawless Transitions** Choose complementary or exact match indoor-outdoor porcelain tiles and pavers to create a seamless, envy-worthy look that endures the ages.

**Modern Life Ready** Stain, scratch, and slip resistant, our durable, low-maintenance porcelain tiles and pavers are a homeowner's dream.

Size	Thickness	CARRARA	CREMA	GREY
12X24 Matte	3/8"	NPRACAR1224	NPRACRE1224	NPRAGRE1224
12X24 Polished	3/8"	NPRACAR1224P	NPRACRE1224P	NPRAGRE1224P
24X48 Matte	3/8"	NPRACAR2448	NPRACRE2448	NPRAGRE2448
24X48 Polished	3/8"	NPRACAR2448P	NPRACRE2448P	NPRAGRE2448P
2X2 Mosaic	3/8"	NPRACAR2X2	NPRACRE2X2	NPRAGRE2X2
16X32 Paver	3/4"		LPAVNPRACRE1632	LPAVNPRAGRE1632
24x24 Paver	3/4"	LPAVNPRACAR2424	LPAVNPRACRE2424	LPAVNPRAGRE2424
3X24 BN Matte	3/8"	NPRACAR3X24BN	NPRACRE3X24BN	NPRAGRE3X24BN
3X24 Polished	3/8"	NPRACAR3X24BNP	NPRACRE3X24BNP	NPRAGRE3X24BNP
13X24 Pool Coping	3/4"	LCOPNPRACAR1324	LCOPNPRACRE1324	LCOPNPRAGRE1324

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	Polished DCOF - < 0.42 Wet Matte DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

The Praia Porcelain Tile Collection features a trio of softly hued colors creams, grays, and a white marble look that complement nearly any decor. Impressively durable and maintenance free, these matte finish porcelain tiles make a signature statement on floors, accent walls, showers, and backsplashes. Use it on floors, walls, shower surrounds, countertops and other spaces where easy care elegance is welcomed. Complete your project with coordinating 3"x24" bullnose tile for a professional finish.

Technical Information

Primary Colors: Cream, Grey, White  
Material Type: Porcelain  
Finish: Matte and Polished  
Polished: Hardness / Mohs 5  
Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation.  
When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

**Disclaimer : Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust. Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo. Variation in shade is an inherent attribute of porcelain tile.  
To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.  
\*No claims accepted after tile installation.

Features At A Glance

- Three neutral colors to suit most installation application
- Bold movement in style of mable
- Copings are also available in 13X24 size

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

