

MSI

Making Dream Surfaces Attainable



Salvage
Porcelain Collection
www.msisurfaces.com

Colors



Brown 6"x40"



Honey 6"x40"



Musk 6"x40"



Red 6"x40"

Size	Thickness	BROWN	HONEY	MUSK	RED
6x40	3/8"	NSALBRO6X40	NSALHON6X40	NSALMUS6X40	NSALRED6X40

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				IV	V3	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

Like treasured family heirlooms, we are naturally drawn to the patina of antique wood floors found in farmhouses and country manors. Made with state of the art digital glazing techniques, our Salvage collection authentically reproduces the grain, texture and color of reclaimed wood. The 6"x40" non-rectified porcelain tiles mirror the length of traditional wood planks, providing countless installation options. Choose from four natural hues, complemented with a matte finish.

Technical Information

Primary Colors: Brown, Honey, Musk, Red
Material Type: Glazed Porcelain
Finish: Matte finish with texture
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Features At A Glance

- Mid level price from Italy
- Glazed Porcelain
- Realistic reclaimed wood planks
- 6x40 non-rectified ink-jet wood plank

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.