





### Colors





Grey 12"x24"

White 12"x24"

Size	Thickness	GREY	WHITE		
12x24	3/8"	NSOPGRE1224	NSOPWHI1224		
3x24	3/8"	NSOPGRE3X24BN	NSOPWHI3X24BN		

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	•	•	•						
LIGHT COMMERCIAL	•	•	•	IV	V2	SCOF - > 0.60 Wet DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
HEAVY COMMERCIAL			•						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed	
Resistant	Resistant	Pressed	Glazed	

A classic beauty with a twist, Veneto introduces a fresh take on vein cut travertine that showcases its luxurious linear movement in several stunning colors. Veneto boasts the most popular sizes in the tile industry offering planks, two rectangles, and a bullnose to create those dreamy floor and wall combinations with ease. Incorporate this elegant travertine look with confidence knowing it is uniquely designed in high quality porcelain.

# Technical Information

Primary Colors: Anthracite, Grey, Maron, White Material Type: Glazed Porcelain, Non-Rectified

Finish: Matte

Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

#### Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

## Features At A Glance

- Non-rectified porcelain from Italy
- Contemporary look with a soft texture
- Full body, glazed tiles at mid level price points
- Ink-Jet Technology

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.





3" x 24" Bullnose



### Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.