

MSI

Making Dream Surfaces Attainable



Tektile

Porcelain Collection

www.msisurfaces.com

Colors



Crosshatch Gray 12"x24"



Crosshatch Ivory 12"x24"



Lineart Gray 12"x24"



Lineart Ivory 12"x24"

Size	Thickness	CROSSHATCH GRAY	CROSSHATCH IVORY	LINEART GRAY	LINEART IVORY
12x24	3/8"	NTEKCROGRA1224	NTEKCROIVO1224	NTEKLINGRA1224	NTEKLINIVO1224
3x24BN	3/8"	NTEKCROGRA3X24BN	NTEKCROIVO3X24BN	NTEKLINGRA3X24BN	NTEKLINIVO3X24BN

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				IV	V2	DCOF - > 0.42 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

Tektile pairs an Italian glazed porcelain tile with all the texture you’d expect from a modern fabric inspired collection. This ultra durable and low maintenance new concept line features three styles a nod to the fabric, linen, and denim looks we love in ivory and gray tones. An intriguing departure from other floor and wall tiles, you can mix and match them to give a wide range of living and commercial spaces a trendy look.

Technical Information

Primary Colors: Beige, Gray
Material Type: Glazed Porcelain
Finish: Matte
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer :

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust. Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo. Variation in shade is an inherent attribute of porcelain tile. To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Features At A Glance

- Rectified Italian ink jet prints for realistic fabric looks
- Two distinct fabric textures all available in two contemporary colors
- Light commercially rated for all installation applications with coordinating BN trim pieces

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 24" Bullnose

