

# Tempest Ceramic Collection

www.msisurfaces.com

# Colors







Beige 13"x13"			Gray 13"x13"				Natural 13"x13"					
Size	Thickness	BEIGE				GRAY			NATURAL			
13x13	3/8"	NTEMBEI1313				NTEMGRE1313			NTEMNAT1313			
18x18	3/8"	NTEMBEI1818			NTEMGRE1818			NTEMNAT1818				
12x24	3/8"	NTEMBEI1224			NTEMGRE1224			NTEMNAT1224				
2x2 MOSAIC	3/8"	NTEMBEI2X2			NTEMGRE2X2			NTEMNAT2X2				
3X13 BN	3/8"	3/8" NTEMBEI3X13BN				NTEMGRE3X13BN			NTEMNAT3X13BN			
APPLICATION	S Flooring	Counters	Wall	PEI Rating	Varia	ation	COF	Breaking Strength		Water Absorption	Hardness	
RESIDENTIAL		۲	۲				DCOF - > 0.42 Wet					
LIGHT COMMERC	IAL	۲			V3	/3		< 275 lbf		> 3-6%	6	
HEAVY COMMERC	IAL			1								
Freeze	C	Chemical Resistance				Rectified/ Non-Rectified			Glazed / Non Glazed			

Durability and elegance come together in the Tempest Collection. Featuring a traditional travertine look in three neutral on trend hues, Beige, Grey, and Natural, this affordable matte finish ceramic tile is understated but not overlooked. Offered in classic 12"x24", as well as popular 13"x13" and 18"x18" formats, Tempest is suitable for a variety of interior residential and light commercial applications including floors, walls, backsplash, and countertops. Give your space warmth and sophistication with the Tempest Collection.

Resistant

# Technical Information

Primary Colors: Beige, Gray Material Type: Ceramic Finish: Matte Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7 Installation 1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a

Non Resistant

less than 33% staggered brick lay is strongly recommended.

# Features At A Glance

• 3 Great colors in wide Variety of sizes and trims

Pressed

- High Variations and with bold movement to
- emulate a cross cut Travertine

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

### Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns. \*No claims accepted after tile installation.

Trim

Glazed



3" x 13" Bullnose



