

MSI

Making Dream Surfaces Attainable

HOTEL
★★★★

Traktion

Porcelain Collection

www.msisurfaces.com

Colors



Calypso Ash12"x24"



Calypso Graphite 12"x24"



Maven Gris 12"x24"



Maven Ivory 12"x24"



Maven Talc 12"x24"

Size	Thickness	ASH	GRAPHITE	GRIS	IVORY	TALC
12X24 Matte	3/8"	NCALASH1224	NCALGRA1224	NMAVGRI1224	NMAVIVO1224	NMAVTAL1224
24X48 Matte	3/8"	NCALASH2448	NCALGRA2448	NMAVGRI2448	NMAVIVO2448	NMAVTAL2448

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	DCOF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				IV	V4	DCOF > 0.42 Matte	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed - 12x24	Glazed
		Rectified - 24x48	

The Traktion Calypso Collection offers style and sophistication to indoor and outdoor spaces. Available in two contemporary neutral colors, these porcelain tiles provide the look of natural stone, which is always on-trend. In addition, the tiles are available in 12"x24" and 24"x48" for added design flexibility. The Calypso Collection boasts MSI's proprietary ZeroSlip™, designed to be exceptionally slip-resistant when wet. These gorgeous, versatile shades of gray suit any interior and architectural style. Use tiles from the Calypso Collection to create a chic backsplash, floor, accent wall, patio, countertop, walkway, and more in residential and light commercial spaces.

Technical Information

Primary Colors: Gray-Dark
Material Type: Porcelain
Finish: Matte
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Features At A Glance

- Unique Large Format 12X24 & 24X48
- 5 Color In a Natural Concrete Look
- Available In a Matte Finishes

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Disclaimer: Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

