

MSI

Making Dream Surfaces Attainable



Veneto
Porcelain Collection
www.msisurfaces.com

Colors



Veneto Gray
12"x24"



Veneto Noce
12"x24"



Veneto Sand
12"x24"



Veneto White
12"x24"



12"x24"



3"x18" Bullnose



3"x24" Bullnose

Size	Thickness	GRAY	NOCE	SAND	WHITE
12x24 Matte	3/8"	NVENEGRA1224	NVENENOC1224	NVENESAN1224	NVENEWHI1224
12X24 Polished	3/8"	NVENGRA1224P-N	NVENNOC1224P-N	NVENSAN1224P-N	NVENWHI1224P-N
3x18BN	3/8"	NVENGRA3X18BNP-N	NVENNOC3X18BNP-N	NVENSAN3X18BNP-N	NVENWHI3X18BNP-N
3x24BN	3/8"	NVENEGRA3X24BN	NVENENOC3X24BN	NVENESAN3X24BN	NVENEWHI3X24BN

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	DCOF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				III	V3	Matte - > 0.42 Wet Polished - < 0.42 Wet	> 275 lbf	< 0.5%	6
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

A classic beauty with a twist, Veneto introduces a fresh take on vein cut travertine that showcases its luxurious linear movement in several stunning colors. Veneto boasts the most popular sizes in the tile industry offering planks, two rectangles, and a bullnose to create those dreamy floor and wall combinations with ease. Incorporate this elegant travertine look with confidence knowing it is uniquely designed in high quality porcelain.

Technical Information

Primary Colors: Brown, Beige, Gray
Material Type: Glazed Porcelain
Finish: Matte & Polished
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Features At A Glance

- Available in 12x24 size
- Available in four unique colors
- Ink Jet Glazed Porcelain

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 18" Bullnose
3" x 24" Bullnose

