

# MSI

Making Dream Surfaces Attainable



Venice  
Porcelain Collection  
[www.msisurfaces.com](http://www.msisurfaces.com)

Colors



Cappuccino 20"x20"



Crema 20"x20"



Noche 20"x20"



Storm 20"x20"

Size	Thickness	CAPPUCCINO	CREMA	NOCHE	STORM
2x2	3/8"	NVENCAP2X2	NVENCRE2X2	NVENNOC2X2	NVENSTO2X2
20x20	3/8"	NVENCAP2020	NVENCRE2020	NVENNOC2020	NVENSTO2020
3x13BN-R	3/8"	NVENCAP3X13BN-R	NVENCRE3X13BN-R	NVENOCE3X13BN-R	NVENSTO3X13BN-R

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Freeze/Thaw	Breaking Strength	Water Absorption	Hardness	Chemical Resistance
RESIDENTIAL				III	V3	SCOF - > 0.60 Wet DCOF - > 0.42 Wet	Resistant	> 275 lbf	< 0.5%	6	Resistant
LIGHT COMMERCIAL											
HEAVY COMMERCIAL											

Imagine a Venetian piazza bathed in sunlight and you can envision the Venice porcelain series. These timeless tone-on-tone tiles radiate warmth and elegance through four monochromatic palettes and supple texture. Mix and match field tiles and 2"x2" mosaics, including a mixed mosaic for added interest. Customize your installation with complimentary bull nose trims.

Technical Information

Primary Colors: Beige, Brown  
Material Type: Glazed Porcelain  
Finish: Matte

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer:

Variation in shade is an inherent attribute of porcelain tile.  
To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.  
\*No claims accepted after tile installation.

Features At A Glance

- Traditional cross cut travertine looks in virtually maintenance free porcelain tiles
- Complete line with rectified floor tiles, mosaics and coordinating bull nose pieces
- High quality porcelain tiles at entry level price points

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 13" Bullnose

