

Colors







Pietra Vezio Beige Polished

Size	Thickness	VEZIO BEIGE	PIETRA VEZIO BEIGE
12x24 Polished	3/8"		NVEZBEI1224P-N
12x24 Matte	3/8"		NVEZBEI1224-N
2x2 Mosaic	3/8"	NVEZBEI2X2	
2x4 Mosaic	3/8"		NVEZBEI2X4P-N
3x18BN	3/8"	NVEZBEI3X18BN-R	NPIEVEZBEI3X18BNP



APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	•	•	•						
LIGHT COMMERCIAL	•	•	•	III	V3	DCOF - < 0.42 Wet	> 275 lbf	< 0.5%	6
HEAVY COMMERCIAL			•						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

A light, neutral palette meets traditional glamour in Pietra Vezio Beige Porcelain. A lively take on Turkish travertine, this stylish tile features a beautiful blend of warm hues and fossilized veining for a look that's hard to resist. Pietra Vezio Beige offers a variety of tile sizes complete with coordinating mosaics and bullnoses in polished and matte finishes.

Technical Information

Primary Colors: Beige

Material Type: Glazed Porcelain Finish: Matte and Polished Polished: Hardeness / Mohs 5 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- Matte and polished finishes
- Multiple sizes with mosaics and bull nose pieces in both finishes
- Ink-jet, rectified porcelains with a subtle texture on matte finish

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.