



Total thickness 6.5MM Core thickness 5.5MM IXPE Backing 1MM Wear Layer 20 mil Plank size 9" x 60" Bevel Painted/Beveled ASTM F2199 (Dimensional Stability) Passes ASTM F1914 (Residual Indentation) Passes (PSI Equivalent > 5,000 lbs.) ASTM F1515 (Light Stability) Passes ASTM 648 (Radiant Panel) >0.45 watts/CM2, NFPA Class 1 ASTM E662 (nbs smoke) < 450 ASTM E2179 (Impact Sound Reductions) ASTM F2196 (Resistance to Chemicals) Passes ASTM D5116 (VOC Requirements) Passes < 100 mg/m ASTM D2047 (Coefficient of Friction) ≥0.6 (Dry) Scratch/Scuff/Abrasion Properties Very Good Phillips Castor Chair @ 100 lbs. Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Residential Warranty Lifetime Light Commercial Warranty 20-Year Commercial Warranty 15-Year	,	,
IXPE Backing Wear Layer Plank size Bevel ASTM F2199 (Dimensional Stability) ASTM F1914 (Residual Indentation) ASTM F1515 (Light Stability) ASTM F1515 (Light Stability) ASTM E662 (nbs smoke) ASTM E662 (nbs smoke) ASTM E2179 (Impact Sound Reductions) ASTM F2179 (Impact Sound Reductions) ASTM F218 (Resistance to Chemicals) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes (25,000 cycles Pastented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty Lifetime Light Commercial Warranty 20 mil 1MM 20 mil 20 mil 1MM 20 mil 20 mil 1MM 20 mil 20 mil 10 Mil 20 mil 10 Mil Passes (PSI Equivalent > 5,000 lbs.) Passes (PSI Equivalent > 5,000 lbs.) Passes ASTM F1515 (Light Stability) Passes 450 72 - drop ceiling / 54 - 6" slab ASTM E2179 (Impact Sound Reductions) A IIC ≥ 26 dB Passes ASTM D5116 (VOC Requirements) Passes < 100 mg/m ≥0.6 (Dry) Scratch/Scuff/Abrasion Properties Passes @ 25,000 cycles Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Residential Warranty Lifetime	Total thickness	6.5MM
Wear Layer20 milPlank size9" x 60"BevelPainted/BeveledASTM F2199 (Dimensional Stability)PassesASTM F1914 (Residual Indentation)Passes (PSI Equivalent > 5,000 lbs.)ASTM F1514 (Heat Stability)PassesASTM F1515 (Light Stability)PassesASTM 648 (Radiant Panel)>0.45 watts/CM2, NFPA Class 1ASTM E662 (nbs smoke)<450	Core thickness	5.5MM
Plank size9" x 60"BevelPainted/BeveledASTM F2199 (Dimensional Stability)PassesASTM F1914 (Residual Indentation)Passes (PSI Equivalent > 5,000 lbs.)ASTM F1514 (Heat Stability)PassesASTM F1515 (Light Stability)PassesASTM 648 (Radiant Panel)>0.45 watts/CM2, NFPA Class 1ASTM E662 (nbs smoke)<450	IXPE Backing	1MM
Bevel Painted/Beveled ASTM F2199 (Dimensional Stability) Passes ASTM F1914 (Residual Indentation) Passes (PSI Equivalent > 5,000 lbs.) ASTM F1514 (Heat Stability) Passes ASTM F1515 (Light Stability) Passes ASTM 648 (Radiant Panel) >0.45 watts/CM2, NFPA Class 1 ASTM E662 (nbs smoke) <450 ASTM (E492-09 / ASTM 989-06) 72 - drop ceiling / 54 - 6" slab ASTM E2179 (Impact Sound Reductions) Δ IIC ≥ 26 dB ASTM F925 (Resistance to Chemicals) Passes ASTM D5116 (VOC Requirements) Passes < 100 mg/m ASTM D2047 (Coefficient of Friction) ≥0.6 (Dry) Scratch/Scuff/Abrasion Properties Very Good Phillips Castor Chair @ 100 lbs. Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Residential Warranty Lifetime Light Commercial Warranty	Wear Layer	20 mil
ASTM F2199 (Dimensional Stability) ASTM F1914 (Residual Indentation) ASTM F1914 (Heat Stability) ASTM F1514 (Heat Stability) Passes ASTM F1515 (Light Stability) Passes ASTM 648 (Radiant Panel) ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM (E492-09 / ASTM 989-06) ASTM F2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes (25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty 20-Year	Plank size	9" x 60"
ASTM F1914 (Residual Indentation) ASTM F1514 (Heat Stability) Passes ASTM F1515 (Light Stability) Passes ASTM 648 (Radiant Panel) ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) Passes ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty Passes (PSI Equivalent > 5,000 lbs.) Passes 3 - 0.450 ASTM Class 1 450 72 - drop ceiling / 54 - 6" slab ASTM F925 (Resistance to Chemicals) Passes ASTM D2047 (Coefficient of Friction) ≥0.6 (Dry) Scratch/Scuff/Abrasion Properties Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Lifetime Light Commercial Warranty	Bevel	Painted/Beveled
ASTM F1514 (Heat Stability) ASTM F1515 (Light Stability) Passes ASTM 648 (Radiant Panel) ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) Passes ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes (25,000 cycles) Installation System Pasidential Warranty Lifetime Light Commercial Warranty Passes Passes Passes Passes Passes (25,000 cycles) FloorScore & Greenguard Lifetime Light Commercial Warranty	ASTM F2199 (Dimensional Stability)	Passes
ASTM F1515 (Light Stability) ASTM 648 (Radiant Panel) ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM (E492-09 / ASTM 989-06) ASTM F2179 (Impact Sound Reductions) ASTM F25 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes Passes Very Good Phillips Castor Chair @ 100 lbs. Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Residential Warranty Lifetime Light Commercial Warranty	ASTM F1914 (Residual Indentation)	Passes (PSI Equivalent > 5,000 lbs.)
ASTM 648 (Radiant Panel) ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM (E492-09 / ASTM 989-06) ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes Passes (25,000 cycles Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty 20-Year	ASTM F1514 (Heat Stability)	Passes
ASTM E662 (nbs smoke) ASTM (E492-09 / ASTM 989-06) ASTM (E492-09 / ASTM 989-06) ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty 20-Year	ASTM F1515 (Light Stability)	Passes
ASTM (E492-09 / ASTM 989-06) ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty 20-Year	ASTM 648 (Radiant Panel)	>0.45 watts/CM2, NFPA Class 1
ASTM E2179 (Impact Sound Reductions) ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty Δ IIC ≥ 26 dB Passes Passes Passes @ 200 mg/m ≥0.6 (Dry) Pery Good Passes @ 25,000 cycles Patented Locking System (Angle / Drop) FloorScore & Greenguard Lifetime	ASTM E662 (nbs smoke)	<450
ASTM F925 (Resistance to Chemicals) ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes < 100 mg/m ≥0.6 (Dry) Very Good Phillips Castor Chair @ 100 lbs. Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty 20-Year	ASTM (E492-09 / ASTM 989-06)	72 - drop ceiling / 54 - 6" slab
ASTM D5116 (VOC Requirements) ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Passes @ 25,000 cycles Installation System Patented Locking System (Angle / Drop) Certifications Residential Warranty Lifetime Light Commercial Warranty Passes < 100 mg/m Very Good Passes @ 25,000 cycles Patented Locking System (Angle / Drop) FloorScore & Greenguard Lifetime	ASTM E2179 (Impact Sound Reductions)	∆ IIC ≥ 26 dB
ASTM D2047 (Coefficient of Friction) Scratch/Scuff/Abrasion Properties Phillips Castor Chair @ 100 lbs. Installation System Certifications Residential Warranty Light Commercial Warranty ≥0.6 (Dry) Very Good Passes @ 25,000 cycles Patented Locking System (Angle / Drop) FloorScore & Greenguard Lifetime 20-Year	ASTM F925 (Resistance to Chemicals)	Passes
Scratch/Scuff/Abrasion Properties Phillips Castor Chair @ 100 lbs. Installation System Certifications Residential Warranty Light Commercial Warranty Very Good Passes @ 25,000 cycles Patented Locking System (Angle / Drop) FloorScore & Greenguard Lifetime 20-Year	ASTM D5116 (VOC Requirements)	Passes < 100 mg/m
Phillips Castor Chair @ 100 lbs. Installation System Certifications Residential Warranty Light Commercial Warranty Passes @ 25,000 cycles Patented Locking System (Angle / Drop) FloorScore & Greenguard Lifetime 20-Year	ASTM D2047 (Coefficient of Friction)	≥0.6 (Dry)
Installation System Patented Locking System (Angle / Drop) Certifications FloorScore & Greenguard Residential Warranty Lifetime Light Commercial Warranty 20-Year	Scratch/Scuff/Abrasion Properties	Very Good
Certifications FloorScore & Greenguard Residential Warranty Lifetime Light Commercial Warranty 20-Year	Phillips Castor Chair @ 100 lbs.	Passes @ 25,000 cycles
Residential Warranty Lifetime Light Commercial Warranty 20-Year	Installation System	Patented Locking System (Angle / Drop)
Light Commercial Warranty 20-Year	Certifications	FloorScore & Greenguard
	Residential Warranty	Lifetime
Commercial Warranty 15-Year	Light Commercial Warranty	20-Year
	Commercial Warranty	15-Year

The XL Prescott Collection by MSI contains no phthalates and uses 100% virgin vinyl.

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.