

ROSWELL

XL STUDIO COLLECTION

LUXURY VINYL FLOORING

Discover the timeless elegance of the XL Studio Collection, featuring stunning 9" x 60" planks. From beachy blonde hues to rich browns, each piece showcases natural knots and grains, delivering the authentic charm of real wood. Domestically sourced in the USA, the extra thick 9MM planks offer exceptional comfort underfoot, making them perfect for high-traffic areas like kitchens and bathrooms. Ideal for both commercial and residential spaces, these planks can be purchased and installed on the same day with no acclimation required. Enjoy a seamless blend of beauty and durability with the XL Studio Collection.



ADLAR RXI ADI AR9X60-9MM-30MII



BOZEMAN RXI BOZMAN9X60-9MM-30MII



DOACK VTRXLDOACK9X60-9MM-30MIL



LARK VTRXLLARK9X60-9MM-30MIL



MALDEN VTRXLMALDEN9X60-9MM-30MIL



QUILLIAN VTRXLQUIIAN9X60-9MM-30MIL



ROSWELL VTRXLROSWEL9X60-9MM-30MIL VTRXLSWICAN9X60-9MM-30MIL



SWILCAN



TAOS VTRXLTAOS9X60-9MM-30MIL



TIFTON VTRXLTIFTON9X60-9MM-30MIL

- · Total thickness: 9MM
- · Wear Layer: 30 Mil
- Plank size: 9"x60"
- · ASTM F2199 (Dimensional Stability): Passes
- · ASTM F1914 (Residual Indentation): Passes
 - (PSI Equivalent > 5,000 lbs.)
- ASTM F1514 (Heat Stability): Passes
- · ASTM F1515 (Light Stability): Passes
- ASTM 648 (Radiant Panel): >0.45 watts/CM2/NFPA Class 1
- ASTM E662 (nbs smoke): <450

- ASTM (E492-09 / ASTM 989-06): 71 -drop ceiling 53 6" slab
- · ASTM E2179 (Impact Sound Reductions): △ IIC ≥ 23 dB
- ASTM F925 (Resistance to Chemicals): Passes
- ASTM D5116 (VOC Requirements): Passes < 100 mgm
- ASTM D2047 (Coefficient of Friction): ≥0.6 (Dry)
- · Scratch/Scuff/Abrasion Properties: Very Good
- · Certifications: FloorScore & Greenquard
- · Residential Warranty: Lifetime
- · Light Commercial Warranty: 30-Year
- · Commercial Warranty: 25-Year





The XL Studio Collection by MSI contains no phthalates and uses 100% virgin vinyl.